

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 March 2001 (01.03.2001)

PCT

(10) International Publication Number
WO 01/14696 A1

(51) International Patent Classification⁷: F01N 3/021, 3/023, 3/025

(21) International Application Number: PCT/EP00/07420

(22) International Filing Date: 31 July 2000 (31.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
99202673.2 19 August 1999 (19.08.1999) EP

(71) Applicant (for all designated States except US): N.V. BEKAERT S.A. [BE/BE]; D.I.E. - 4011, Bekaertstraat 2, B-8550 Zwevegem (BE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MARRECAU, Willy [US/US]; 37, Huntington Road, Rome, GA 30165 (US).

(74) Agent: MESSELY, Marc; D.I.E. 4011, Bekaertstraat 2, B-8550 Zwevegem (BE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DIESEL EXHAUST PARTICULATE FILTER SYSTEM



(57) Abstract: A method is provided for regenerating a filter of a diesel exhaust particulate filter system (10). The method comprises as steps: a) providing at least one porous membrane (16, 18); b) using said membrane (16, 18) as filter during a filtration period; c) using said membrane (16, 18) as a surface combustion burner membrane during a regeneration period.

WO 01/14696 A1